



Fyrkantör och fästjärn

- Fyrkantör levereras i standardlängder om 6 m.
- Platt- och vinkeljärn levereras i fallande längder 4-6 m.
- Rostfritt 2333 - 304, Syrafast 2343 - 316



Dimension	Artikelnummer
Fyrkantör slipade	
	Rostfritt
20 x 20 x 1.5 mm	83-001
30 x 30 x 1.5 mm	83-003
40 x 40 x 2.0 mm	83-005
50 x 50 x 2.0 mm	83-007
Plattstål	
	Rostfritt
20 x 3 mm	83-072
20 x 4 mm	83-073
25 x 3 mm	83-075
25 x 5 mm	83-077
30 x 4 mm	83-079
30 x 5 mm	83-080
40 x 4 mm	83-082
40 x 5 mm	83-083
50 x 5 mm	83-086
Vinkelstål	
	Rostfritt
20 x 20 x 3 mm	83-120
30 x 30 x 3 mm	83-122
30 x 30 x 4 mm	83-123
40 x 40 x 4 mm	83-124
50 x 50 x 5 mm	83-125



I . A . C . Komponenter AB

International Automation Components

P.O Box 60, S-566 22 Habo Phone: +46 (0)36 477 00 Fax: +46 (0)36 477 15
E-mail: habo@iackomp.se www.iackomp.se