


Flow Regulators & Gauges

Flow regulators

- Meiflow • The flow regulator produce fixed flow even if the pressure changes

Gauges

- We offer small plastic and metal gauges up to process gauges in stainless steel and for high pressure



Size	Part.No.
Flow regulator Meiflow	
Water 400 0.04 - 0.4 lit/min	stainless PN 40 71-011
Water 1 0.1 - 1.0 lit/min	stainless PN 40 71-012
Air 5 1.0 - 5.0 lit/min	stainless PN 40 71-014
Water 400 0.04 - 0.4 lit/min	delrin 71-051
Water 1 0.1 - 1.0 lit/min	delrin 71-052
Indicator complete	
W 200 Part 7-8,10-15	71-055
W 400 Part 7-8,10-15	71-056
W1 Part 7-8,10-15	71-057
A5 Part 7-8,10-15	71-058
Indicator	
W 400 Part 12	71-063
W 1 Part 12	71-064
Membrane	
W200, W400, W1, A5 Part 6	71-070
Measuring plug	
W200, W400, A5 Part 7	71-071
W1 Part 7	71-072
Float	
W200, W400, W1, Part 8	71-075
O-ring	
Part 10	71-080
Part 11	71-081
Flow disc	
W1, Part 5	71-069
Gauge with connection down	
0- 6 bar 40 mm 1/8" plastic	22-102
0-12 bar 40 mm 1/8" plastic	22-104
Gauge with connection back	
0- 4 bar 40 mm 1/8" plastic	22-105
0- 6 bar 40 mm 1/8" plastic	22-106
0-10 bar 40 mm 1/8" plastic	22-107
0-12 bar 40 mm 1/8" plastic	22-108
Gauge with connection back	
0-4 bar 40 mm 1/8" metal	22-005
0-4 bar 63 mm 1/8" metal	22-006
0-16 bar 40 mm 1/8" metal	22-003



I . A . C . Komponenter AB

International Automation Components

P.O Box 60, S-566 22 Habo Phone: +46 (0)36 477 00 Fax: +46 (0)36 477 15

E-mail: habo@iackomp.se www.iackomp.se

Flow Regulators & Gauges

Flow regulators

- Meiflow • The flow regulator produce fixed flow even if the pressure changes

Gauges

- We offer small plastic and metal gauges up to process gauges in stainless steel and for high pressure



Size	Part.No.
Gauge max 400 bar Stainless body	
Ø 63 mm, 1/4" Connection brass, bottom entry, *	22-410
Ø 63 mm, 1/4" Connection brass, back entry, *	22-415
Gauge max 400 bar Stainless body	
Ø 63 mm, 1/4" Connection stainless, bottom entry, *	22-420
Ø 63 mm, 1/4" Connection stainless, back entry, *	22-425
Gauge max 1000 bar Stainless body	
Ø 63 mm, 1/4" Connection stainless, bottom entry, *	22-430
Ø 63 mm, 1/4" Connection stainless, back entry, *	22-435
Gauge max 400 bar Stainless body	
Ø 100 mm, 1/2" Connection stainless, bottom entry, *	22-440
Ø 100 mm, 1/2" Connection stainless, back entry, *	22-445
Gauge max 1000 bar Stainless body	
Ø 100 mm, 1/2" Connection stainless, bottom entry, *	22-450
Ø 100 mm, 1/2" Connection stainless, back entry, *	22-455
* Please advice pressure rate at order	
Digital display	
For Pressuretransmitter 4-20mA	22-471



I . A . C . Komponenter AB

International Automation Components

P.O Box 60, S-566 22 Habo Phone: +46 (0)36 477 00 Fax: +46 (0)36 477 15

E-mail: habo@iackomp.se www.iackomp.se